

DELTA 3 Max (2048Wh)

Colour: Black and Grey
Capacity: 2048Wh
Net Weight: Approx. 20.3 kg
Dimensions: 494 × 239 × 305 mm
Total Output Ports: 9
Total Output Power: 2674W Max
UPS: 10 ms
Warranty Period: 3+2 years
Volume: 600W ≤ 25 dB



AC Output

Number of AC Outlets	Output Priority	Max AC Output
4	N/A	2400W
Surge Output	X-Fusion	Max X-Boost Output
4800W	N/A	3200W
Output Voltage		
230V~50Hz, 2400W Total 10A Max per port (×4)		

DC Output

Number of DC Outlets	USB-A	USB-C
5	1 × 18W Max	1 × 100W Max 2 × 30W Max (Total 30W)
12V DC Output		
126W Max Car Power Output × 1:12.6V==10A		

Input

Utility Power Charging	Input Voltage	0-80% Charge Time
2300W (Depending on Input Voltage)	220-240V~10A 50/60Hz	51 min
Solar Charging	Alternator Charging	0-100% Charge Time
500W	500W Max Through XT60 Port	68 min
Generator Charging	Car Charging	
2400W Max	12V/24V==8A	

Battery

Battery Chemistry	Type of Extra Battery Ports	CTC Technology
LFP	N/A	CTC
Extra Battery Compatibility	Number of Extra Battery Ports	Max Capacity with Extra Battery
N/A	N/A	N/A

Connections

Screen	Wi-Fi	Bluetooth	App
Yes	Yes	Yes	Yes

Operating Conditions

Operating Altitude: ≤3000 m	Discharge Temperature: -10-45°C
Charge Temperature: 0-45°C	Storage Temperature: -10-45°C